

**MULTIPURPOSE TRAILERS****BALE / PLATFORM****CHARACTERISTICS**

- Highly robust frame made of Ferpinta® structural tube;
- Adjustable/removable (front) mesh protections (option);
- Toolbox L (500x400x400) and water tank (hand-washing) - standard features;
- Stretching pulleys every 2 m for better cargo securing;
- Bottom in 4mm steel sheet.

Agricultural platforms intended primarily for transporting bales, regardless of their shape. 2 or 3 axle models, available with bogie, axle+axle, axle+bogie or tridem suspension, in order to choose the best option for the purpose for which it is intended.

It has adjustable and removable mesh protections, stretching pulleys every 2 m and side screens for better storage of the transported cargo.

**BALES****PALLETS**

## STANDARD PRODUCT

Characteristics	Uni.	TWO AXLES			THREE AXLES	
		HPT 8	HPT 10	HPG 8	HPGT 10	HPT 10Tridem
Box/Body (outside)	-	-	-	-	-	-
Length	m	8,00	10,00	8,00	10,00	10,00
Width	m	2,43	2,43	2,43	2,43	2,43
Indicative empty weight	t	4,14	4,80	3,74	5,00	6,00
Payload	t	1400	1400	13,50	20,00	21,00
<b>Dimensions</b>						
Total length	m	9,80	11,80	10,01	1200	1151
Total width	m	2,43	2,43	2,43	2,43	2,43
Total height	m	1,18	1,19	1,20	1,16	1,18
Platform height, unladen	m	1,18	1,19	1,20	1,16	1,18
<b>Suspension, axles and tyres</b>						
Suspension type	-	Bogie (2 axles)	Bogie (2 axles)	-	Axle + Bogie	Tridem (3 axles)
Axle type	-	2 Fixed axles	2 Fixed axles	Dolly axle (1st) and Fixed (2nd)	Dolly axle (1st) and Fixed (2nd and 3rd)	Free-steering axles (1st and 3rd)
Axle square - (number of studs)	mm - (n.º)	100 - (8)	100 - (8)	100 - (8)	100 - (8)	130 - (10)
Braking hubs	mm	400 x 80	400 x 80	400 x 80	400 x 80	400x120
Axle track	mm	1850	1850	1850	1850	1950
Wheels	-	435/50 R19.5	435/50 R19.5	435/50 R19.5	435/50 R19.5	435/50 R19.5

## INCREASINGLY VERSATILE...

For any equipment, we have several options available with which you can equip your standard product. In this case, we highlight the L and XL mesh protections, the bottom in 5/7 mm anti-slip steel grating, the possibility of configuring the wheels and axles, multiple types of extra lighting and additional accessories.

**Follow us:**  
herculano.pt



**Herculano, S.A.**  
Rua da Indústria, 3720-051 Loureiro  
Oliveira de Azeméis, Portugal

**General**  
E: herculano@ferpinta.pt  
T: +351 256 661 900  
M: +351 965 964470  
F: +351 256 692 497

**Commercial**  
E: dep.comercial.herculano@ferpinta.pt  
T: +351 256 661 913  
F: +351 256 692 497