



Herculano

GRUPO FERPINTA



MULTIPURPOSE TRAILERS

MB

Single axle models with single-wheel, ideal for transport in mountain areas, with a MB trailer box that provides higher stability and maneuverability, due to the low center of gravity. Backwards tipping semi-trailers with removable sidewalls for a quick adaptation to multiple needs.

CHARACTERISTICS

- Single axle and single-wheel semi-trailers, with a loading capacity up to 3.5t;
- MB trailer box backwards tipping with an angle up to 40°;
- Removable sidewall;
- Support leg (fuse).



AGRICULTURE



MISCELLANEOUS
SERVICES

WHY CHOOSE HERCULANO PRODUCTS?

01

Over 50 years of experience

02

Produces equipment tailored to your needs

03

Field technical assistance (direct or through local partners)

04

Manuals and spare parts catalogue (to facilitate the parts exchange process)

05

24-month warranty

STANDARD PRODUCT

Characteristics	Uni.	MB 1875	MB 3200	MB 3500	MB 3800
Box/Body (outside)	-	-	-	-	-
Length	m	2,25	2,25	2,40	2,60
Width	m	1,40	1,40	1,55	1,55
Height	m	0,50	0,50	0,50	0,50
Indicative empty weight	t	0,75	0,63	0,79	0,85
Payload	t	1,88	3,20	3,50	3,50
Capacity	m³	1,10	1,10	1,10	1,50
Dimensions					
Interior of the box/body	-	-	-	-	-
Length	m	2,16	2,16	2,31	2,51
Width	m	1,32	1,32	1,47	1,47
Height	m	0,71	0,71	0,71	0,71
Total length	m	3,48	3,48	3,65	3,86
Total width	m	1,50	1,50	1,65	1,65
Total height	m	1,37	1,37	1,37	1,45
Platform height, unladen	m	0,66	0,66	0,66	0,78
Total height (at max. tipping angle)	m	2,51	2,61	2,61	1,49
Suspension, axles and tyres					
Axle type	-	Fixed single axle	Fixed single axle	Fixed single axle	Fixed single axle
Axle square - (number of studs)	mm - (n.º)	50 - (6)	50 - (6)	60 - (6)	60 - (6)
Braking hubs	mm	250 x 60	250 x 60	300 x 60	300 x 60
Axle track	mm	1200	1200	1300	1300
Wheels	-	10.0/75-15.3 14PR	10.0/75-15.3 14PR	10.0/75-15.3 14PR	11.50/80-15.3 14PR
Tipping details					
Tipping angle	-	40°	40°	40°	38°
Tipping cylinder stages	-	3	3	3	3
Tipping cylinder diameter/height	mm	140/549	140/549	140/549	140/549
Tipping cylinder - pressure/oil requirement	bar/l	180/3	180/3	180/3	180/3

INCREASINGLY VERSATILE...

For any equipment, we have several options available with which you can equip your standard product. In this case, we highlight the possibility of changing wheels and adding the manual pump for hydraulic support leg.

Follow us:
herculano.pt

Herculano, S.A.
Rua da Indústria, 3720-051 Loureiro
Oliveira de Azeméis, Portugal

General
E: herculano@ferpinta.pt
T: +351 256 661 900
M: +351 965 964 470
F: +351 256 692 497

Commercial
E: dep.comercial.herculano@ferpinta.pt
T: +351 256 661 913
F: +351 256 692 497

