



CHARACTERISTICS

- Single axle and single-wheel trailers, with a loading capacity up to 3.9t;
- Three-side tipping trailer metallic box;
- Possibility of adding additional extensions (in the selected models);
- Stanchion gutters;
- Removable front mesh protection;
- Support leg (fuse);
- Height adjustable drawbar.

MULTIPURPOSE TRAILERS SIET

The SIET trailers are available in 18 different models, with a single axle and single wheels, which are defined by their versatility and maneuverability, thus providing greater multifunctionality.



SILAGE



CEREALS



FRUITS/
VEGETABLES



MISCELLANEOUS
SERVICES

STANDARD PRODUCT

Characteristics	Uni.	S1ET 1875	S1ET 2500	S1ET 3000
Box/Body (outside)	-	-	-	-
Length	m	2,25	2,50	2,70
Width	m	1,40	1,55	1,55
Height	m	0,50	0,50	0,50
Indicative empty weight	t	0,56	0,69	0,74
Payload	t	1,88	2,50	3,00
Capacity	m ³	1,40	1,80	2,00
Dimensions				
Interior of the box/body	-	-	-	-
Length	m	2,16	2,41	2,61
Width	m	1,31	1,46	1,51
Height	m	0,50	0,50	0,50
Total length	m	3,32	3,56	3,86
Total width	m	1,51	1,67	1,67
Total height	m	1,75	1,70	1,70
Platform height, unladen	m	0,90	0,85	0,85
Total height (at max. tipping angle)	m	2,78	2,85	3,00
Suspension, axles and tyres				
Axle type	-	Fixed single axle	Fixed single axle	Fixed single axle
Axle square - (number of studs)	mm - (n.º)	50 - (6)	60 - (6)	60 - (6)
Braking hubs	mm	250 x 60	300 x 60	300 x 60
Axle track	mm	1 200	1 300	1 300
Wheels	-	10.0/75-15.3 14PR	10.0/75-15.3 14PR	10.0/75-15.3 14PR
Tipping details				
Tipping angle backwards/sides	-	44 ° / 45°	40° / 45°	39° / 45°
Tipping cylinder stages	-	3	3	3
Tipping cylinder diameter/height	mm	110/580	110/582	110/687
Tipping cylinder - pressure/oil requirement	bar/l	180/3	180/3	180/642

S1ET 3100	S1ET 3125	S1ET 3200	S1ET 3500	S1ET 3900
-	-	-	-	-
2,50	2,85	2,25	2,70	2,85
1,55	1,70	1,40	1,55	1,70
0,50	0,50	0,50	0,50	0,50
0,69	0,66	0,56	0,74	0,81
3,10	3,13	3,20	3,50	3,90
1,80	2,20	1,40	2,00	2,20
-	-	-	-	-
2,41	2,76	2,16	2,61	2,76
1,46	1,61	1,31	1,51	1,61
0,50	0,50	0,50	0,50	0,50
3,56	3,98	3,32	3,86	3,98
1,67	1,81	1,51	1,67	1,81
1,70	1,76	1,75	1,70	1,76
0,85	0,88	0,90	0,85	0,88
2,85	3,12	2,78	3,00	3,12
Fixed single axle	Fixed single axle	Fixed single axle	Fixed single axle	Fixed single axle
60 - (6)	60 - (6)	50 - (6)	60 - (6)	60 - (6)
300 x 60	300 x 60	250 x 60	300 x 60	300 x 60
1 300	1 400	1 200	1 300	1 300
10.0/75-15.3 14PR	10.0/75-15.3 14PR	10.0/75-15.3 14PR	10.0/75-15.3 14PR	11.50/80-15.3 14PR
40° / 45°	38° / 45°	44 ° / 45°	39° / 45°	38° / 45°
3	3	3	3	3
110/583	110/687	110/581	110/687	110/687
180/3	180/642	180/3	180/642	180/642

INCREASINGLY VERSATILE...

For any equipment, we have several options available with which you can equip your standard product.
In this case, we highlight the additional extensions and the possibility of including a full opening double door or a grain chute.

STANDARD PRODUCT

Models that can be fitted with extensions

Characteristics	Uni.	S1ET 3500+	S1ET 3500++	S1ET 4100	S1ET 5000
Box/Body (outside)	-	-	-	-	-
Length	m	3,00	3,20	3,00	3,20
Width	m	1,60	1,85	1,60	1,85
Height	m	0,50	0,50	0,50	0,50
Indicative empty weight	t	0,88	1,02	0,88	1,02
Payload	t	3,50	3,50	4,10	5,00
Capacity	m ³	2,20	2,70	2,20	2,70
Dimensions					
Interior of the box/body	-	-	-	-	-
Length	m	2,91	3,11	2,91	3,11
Width	m	1,51	1,76	1,51	1,76
Height	m	0,50	0,50	0,50	0,50
Total length	m	4,13	4,53	4,13	4,53
Total width	m	1,71	1,95	1,71	1,95
Total height	m	1,76	1,79	1,76	1,79
Platform height, unladen	m	0,88	0,92	0,88	0,92
Total height (at max. tipping angle)	m	3,06	3,46	3,06	3,46
Suspension, axles and tyres					
Axle type	-	Fixed single axle	Fixed single axle	Fixed single axle	Fixed single axle
Axle square - (number of studs)	mm - (n.º)	60 - (6)	70 - (6)	60 - (6)	70 - (6)
Braking hubs	mm	300 x 60	300 x 60	300 x 60	300 x 60
Axle track	mm	1300	1500	1300	1500
Wheels	-	11.50/80-15.3 14PR	11.50/80-15.3 14PR	11.50/80-15.3 14PR	11.50/80-15.3 16PR
Tipping details					
Tipping angle backwards/sides	-	45° / 45°	42° / 45°	45° / 45°	42° / 45°
Tipping cylinder stages	-	4	4	4	4
Tipping cylinder diameter/height	mm	130/840	130/840	130/840	130/840
Tipping cylinder - pressure/oil requirement	bar/l	180/3,3	180/3,3	180/3,3	180/3,3

S1ET 5000+	S1ET 5200	S1ET 5200+	S1ET 6000	S1ET 8000	S1ET 8000+
-	-	-	-	-	-
3,50	3,50	3,80	4,00	4,60	5,00
1,90	2,00	2,00	2,20	2,30	2,40
0,50	0,50	0,50	0,50	0,50	0,50
1,12	1,10	1,24	1,34	1,98	2,50
5,00	5,20	5,20	6,00	8,00	8,00
3,10	3,30	3,60	4,10	5,00	5,70
-	-	-	-	-	-
3,41	3,41	3,71	3,91	4,51	4,91
1,81	1,91	1,91	2,11	2,21	2,31
0,50	0,50	0,50	0,50	0,50	0,50
4,85	4,87	5,17	5,39	6,02	6,37
1,96	2,06	2,06	2,30	2,40	2,50
2,01	1,98	1,99	1,96	2,08	2,12
1,00	0,99	0,97	0,93	1,05	1,09
3,64	3,63	3,67	4,18	4,40	4,71
Fixed single axle	Fixed single axle	Fixed single axle	Fixed single axle	Fixed single axle	Fixed single axle
70 - (6)	70 - (6)	70 - (6)	80 - (6)	90 - (8)	90 - (8)
300 x 60	300 x 60	300 x 60	300 x 60	400 x 80	400 x 80
1600	1600	1600	1600	1700	1750
12.50/80-15.3 14PR	12.50/80-15.3 14PR	12.50/80-15.3 14PR	435/50 R19.5	385/65 R22.5	385/65 R22.5
38°/ 45°	38°/ 45°	45°/ 45°	42°/ 45°	38°/ 45°	42°/ 45°
4	4	5	5	6	7
130/840	130/840	193/1491	150/1050	170/1237	193/1491
180/3,3	180/3,3	180/7,5	180/6,5	180/9	180/13,5

INCREASINGLY VERSATILE...

For any equipment, we have several options available with which you can equip your standard product. In this case, we highlight the additional extensions and the possibility of including a full opening double door or a grain chute.







Follow us:
herculano.pt



Herculano, S.A.
Rua da Indústria, 3720-051 Loureiro
Oliveira de Azeméis, Portugal

General
E: herculano@ferpinta.pt
T: +351 256 661 900
M: +351 965 964 470
F: +351 256 692 497

Commercial
E: dep.comercial.herculano@ferpinta.pt
T: +351 256 661 913
F: +351 256 692 497